



Material:

- Locking unit: Zinc, zinc plated, steel, zinc plated and glass fibre reinforced polyamide (PA6GF30), black.
- Safety cam: Glass fibre reinforced polyamide (PA6GF30), black.
- Roller cam: Zinc, zinc plated and glass fibre reinforced polyamide (PA6GF30), black.

References, Accessories:

- Handle: Page 2-310a, 2-310b and 2-310c.

Notes, Tests:

Products are available on request only.

*HVAC = Heating, Ventilation and Air Conditioning.

Safety catch - system Klima-flex for HVAC* applications is used for pressurized HVAC units. To prevent doors from opening up without control, the safety catch secondary cam catches the door while positive air pressure escapes. When the secondary knob is turned, the door is opened safely. When operating the latch during closing, the safety catch automatically resets. The safety catch is compatible with all handles in the Klima-flex 1 system (K1).

Safety Catch - System KLIMA-FLEX

P/N	A-B Min	A-B Max	C-D Min	C-D Max	Description - version
265078-T25H	18	30	32	38	Right
265078-T25V	18	30	32	38	Left
265078-T40H	18	45	47	53	Right
265078-T40V	18	45	47	53	Left
265078-T50H	18	55	57	63	Right
265078-T50V	18	55	57	63	Left
265078-T85H	18	80	82	88	Right
265078-T85V	18	80	82	88	Left