



Material:

- Steel, zinc plated or stainless steel (304).
- Protective cap: PVC.

References, Accessories:

- Rods: Page 2-540, 2-541 and 2-545.

Three-point cams for use with housings with internal limitation of rotation. Stroke: 20 mm. Supplied with E-clips. 096001 is a protective plastic cap for cams. The cap fits on the end of the cam and will prevent scratching of coated surfaces, prevent rattling and make cams operate smoother.

*=Straight cam. Other lengths and versions available on request.

C = Housing length.

H = Outside face to engagement point of cam.

Three-Point Cam Without Projection

P/N Steel	P/N SS (304)	H-measurement of cam below.				
		C=12	C=18	C=30	C=45	C=56
2321S01-U	2330S01-U	--	4	16	31	42
2321S02-U	2330S02-U	--	6	18	33	44
2321S03-U	2330S03-U	2	8	20	35	46
2321S04-U	2330S04-U	4	10	22	37	48
2321S05-U	2330S05-U	6	12	24	39	50
2321S07-U	2330S07-U	8	14	26	41	52
2321S08-U	2330S08-U	10	16	28	43	54
2321S09-U *	2330S09-U *	12	18	30	45	56
2321S10-U	2330S10-U	14	20	32	47	58
2321S11-U	2330S11-U	16	22	34	49	60
2321S12-U	2330S12-U	18	24	36	51	62
2321S14-U	2330S14-U	20	26	38	53	64
2321S15-U	2330S15-U	22	28	40	55	66
2321S16-U	2330S16-U	24	30	42	57	68
2321S17-U	2330S17-U	26	32	44	59	70
2321S18-U	2330S18-U	28	34	46	61	72
2321S20-U	2330S20-U	30	36	48	63	74
2321S21-U	2330S21-U	32	38	50	65	76
2321S22-U	2330S22-U	34	40	52	67	78
2321S23-U	2330S23-U	36	42	54	69	80
2321S24-U	2330S24-U	38	44	56	71	82
2321S29-U	2330S29-U	40	46	58	73	84
2321S28-U	2330S28-U	42	48	60	75	86
2321S27-U	2330S27-U	44	50	62	77	88
096001	Protective plastic cap for cams					